

Fine Cut F6.01

Fine polishing compound, silicone-oil-free

Intelligent machine polish of the latest generation with unique aluminium oxide quality. The intelligent grain size ensures very quick, complete removal of wash system scratches and similar traces of use and gives the paintwork a long-lasting deep sheen. Sanding marks left behind by 2500 grade sanding media are removed effortlessly. Fine Cut F6.01 is therefore ideally suited for perfect reconditioning of medium to heavily weathered paintwork. Perfectly coordinated for the treatment of scratch-proof paint.

Cut: 6,0

Gloss: 7,0

Areas of use

Paintwork on cars, commercial vehicles, motor cycles, etc.

Recommendations for use

Apply the fine polishing compound to the polishing pad (Fine Cut Pad or lambswool pad) and polish the precleaned surface with max. 2.000 rpm crosswise. The cleaning effect can be varied by means of pressure, polishing medium and rpm. At the start of the polishing process we recommend working with greater pressure at a lower speed. In the further course, reduce the pressure and polish to a high gloss at a higher speed. The remaining polish residues can be removed easily with our Profi ultrasonic cut microfibre cloth. Remove any streaks or traces of polish with Micro Cut M3.02.

Container

Item no. *Container*

405250	250 ml
405250US	250 ml
405001	1 l
405001US	1 l
405005US	5 l

Warnings

Shake before using. Before using, check suitability and compatibility. Do not use on hot surfaces. Protect against frost and excessive heat.

Notice

This product information can advise you only without obligation. Liability on our part can not be derived. Please check whether the product is suitable for your application. We will be pleased to assist you.